

## Don & Low Ltd

Glamis Road  
Forfar  
Angus DD8 1EY

Tel: 01307 452600 Fax: 01307 452610

e-mail: nonwovens@donlow.co.uk

website: www.donlow.co.uk



**Agrément Certificate**

**03/4003**

Product Sheet 6

### DON & LOW ROOF TILE UNDERLAYS

### BREATHABLE FRAMETX MAXI FOR USE IN TIMBER FRAME CONSTRUCTION

This Agrément Certificate Product Sheet<sup>(1)</sup> relates to Breathable FrameTX Maxi<sup>(2)</sup>, for use in timber frame walls with a cavity and a masonry outer leaf, weatherboarding or tile/slate cladding.

(1) Hereinafter referred to as 'Certificate'.

(2) FrameTX Maxi is a registered trademark of Don & Low Limited.

#### CERTIFICATION INCLUDES:

- factors relating to compliance with Building Regulations where applicable
- factors relating to additional non-regulatory information where applicable
- independently verified technical specification
- assessment criteria and technical investigations
- design considerations
- installation guidance
- regular surveillance of production
- formal three-yearly review.



#### KEY FACTORS ASSESSED

**Weathertightness** — the product will contribute to protecting a wall against water penetration (see section 6).

**Risk of condensation** — the product has low resistance to water vapour transmission and can contribute to reducing the risk of interstitial condensation (see section 7).

**Strength** — the product has adequate strength to resist damage during the construction of walls (see section 8).

**Durability** — the product will have a life equal to that of the building in which they are installed (see section 11).



The BB BBA has awarded this Certificate to the company named above for the product described herein. This product has been assessed by the BBA as being fit for its intended use provided it is installed, used and maintained as set out in this Certificate.

On behalf of the British Board of Agrément

Date of Second issue: 26 March 2018

John Albon – Head of Approvals  
Construction Products

Claire Curtis-Thomas  
Chief Executive

Originally certificated on 5 March 2014

The BBA is a UKAS accredited certification body – Number 113.

The schedule of the current scope of accreditation for product certification is available in pdf format via the UKAS link on the BBA website at www.bbacerts.co.uk  
Readers are advised to check the validity and latest issue number of this Agrément Certificate by either referring to the BBA website or contacting the BBA direct.

#### British Board of Agrément

Bucknalls Lane  
Watford  
Herts WD25 9BA

©2018

tel: 01923 665300  
clientservices@bbacerts.co.uk  
www.bbacerts.co.uk

## Regulations

In the opinion of the BBA, Breathable FrameTX Maxi for use in timber frame construction, if installed, used and maintained in accordance with this Certificate, can satisfy or contribute to satisfying the relevant requirements of the following Building Regulations (the presence of a UK map indicates that the subject is related to the Building Regulations in the region or regions of the UK depicted):



### The Building Regulations 2010 (England and Wales) (as amended)

<b>Requirement:</b>	<b>C2(b)</b>	<b>Resistance to moisture</b>
Comment:		The product will contribute to a wall satisfying this Requirement. See section 6.1 of this Certificate.
<b>Requirement:</b>	<b>C2(c)</b>	<b>Resistance to moisture</b>
Comment:		The product can contribute to limiting the risk of condensation. See section 7.1 of this Certificate.
<b>Regulation:</b>	<b>7</b>	<b>Materials and workmanship</b>
Comment:		The product is acceptable. See section 11 and the <i>Installation</i> part of this Certificate.



### The Building (Scotland) Regulations 2004 (as amended)

<b>Regulation:</b>	<b>8(1)</b>	<b>Durability, workmanship and fitness of materials</b>
Comment:		The use of the product satisfies this Regulation. See section 11 and the <i>Installation</i> part of this Certificate.
<b>Regulation:</b>	<b>9</b>	<b>Building standards applicable to construction</b>
Standard:	3.10	Precipitation
Comment:		The product will contribute to a wall satisfying clauses 3.10.1 <sup>(1)(2)</sup> and 3.10.5 <sup>(1)(2)</sup> of this Standard. See section 6.1 of this Certificate.
Standard:	3.15	Condensation
Comment:		The product can contribute to limiting the risk of condensation with reference to clauses 3.15.1 <sup>(1)</sup> and 3.15.4 <sup>(1)</sup> of this Standard. See section 7.1 of this Certificate.
Standard:	7.1(a)(b)	Statement of sustainability
Comment:		The product can contribute to satisfying the relevant requirements of Regulation 9, Standards 1 to 6, and therefore will contribute to a construction meeting a bronze level of sustainability as defined in this Standard.
<b>Regulation:</b>	<b>12</b>	<b>Building standards applicable to conversions</b>
Comment:		Comments in relation to the product under Regulation 9, Standards 1 to 6, also apply to this Regulation, with reference to clause 0.12.1 <sup>(1)(2)</sup> and Schedule 6 <sup>(1)(2)</sup> .

(1) Technical Handbook (Domestic).

(2) Technical Handbook (Non-Domestic).



### The Building Regulations (Northern Ireland) 2012 (as amended)

<b>Regulation:</b>	<b>23(a)(i)</b>	<b>Fitness of materials and workmanship</b>
Comment:	<b>(iii)(b)(i)</b>	The product is acceptable. See section 11 and the <i>Installation</i> part of this Certificate.
<b>Regulation:</b>	<b>28(b)</b>	<b>Resistance to moisture and weather</b>
Comment:		The product will contribute to a wall satisfying this Regulation. See section 6.1 of this Certificate.
<b>Regulation:</b>	<b>29</b>	<b>Condensation</b>
Comment:		The product can contribute to limiting the risk of condensation. See section 7.1 of this Certificate.

# Construction (Design and Management) Regulations 2015

## Construction (Design and Management) Regulations (Northern Ireland) 2016

Information in this Certificate may assist the client, designer (including Principal Designer) and contractor (including Principal Contractor) to address their obligations under these Regulations.

See section: 1 *Description of this Certificate.*

### Additional Information

#### NHBC Standards 2018

In the opinion of the BBA, Breathable FrameTX Maxi for use in timber frame construction, if installed, used and maintained in accordance with this Certificate, can satisfy or contribute to satisfying the relevant requirements in relation to *NHBC Standards*, Chapter 6.2 *External timber framed walls*.

#### CE marking

The Certificate holder has taken the responsibility of CE marking the product in accordance with harmonised European Standard BS EN 13859-2 : 2014. An asterisk (\*) appearing in this Certificate indicates that data shown are given in the manufacturer's Declaration of Performance.

### Technical Specification

#### 1 Description

Breathable FrameTX Maxi for use in timber frame construction is a composite structure, comprising water-vapour-permeable film and two layers of nonwoven polypropylene fabrics. The product has the nominal characteristics given in Table 1.

*Table 1 Nominal characteristics*

Characteristic (unit)	FrameTX Maxi
Thickness (mm)	0.43
Mass per unit area* ( $\text{g}\cdot\text{m}^{-2}$ )	102
Roll length* (m)	50
Roll width* (m)	1.0/1.5 <sup>(1)</sup>
Colour	
upper	Various
lower	Various
Tensile strength* ( $\text{N}\cdot 50\text{ mm}^{-1}$ )	
longitudinal	250
transverse	140
Elongation* (%)	
longitudinal	60
transverse	70
Tear resistance* (N)	
longitudinal	100
transverse	95
Resistance to penetration of air ( $\text{m}^3\cdot\text{m}^2\text{h}^{-1}50\text{Pa}^{-1}$ )	0.01
Watertightness*	
unaged	W1
aged <sup>(2)</sup>	W1
Equivalent air layer thickness* ( $S_d$ )(m)	0.029
Vapour resistance ( $\text{MN}\cdot\text{s}\cdot\text{g}^{-1}$ )	0.145

(1) Other widths are available.

(2) Aged in accordance with BS EN 13859-2 : 2014, Annex C.

## 2 Manufacture

2.1 The membrane is manufactured by lamination of a water-vapour-permeable film between two layers of non-woven spunbonded polypropylene to form a flexible, vapour-permeable membrane.

2.2 As part of the assessment and ongoing surveillance of product quality, the BBA has:

- agreed with the manufacturer the quality control procedures and product testing to be undertaken
- assessed and agreed the quality control operated over batches of incoming materials
- monitored the production process and verified that it is in accordance with the documented process
- evaluated the process for management of nonconformities
- checked that equipment has been properly tested and calibrated
- undertaken to carry out the above measures on a regular basis through a surveillance process, to verify that the specifications and quality control being operated by the manufacturer are being maintained.

2.3 The management system of Don & Low Ltd has been assessed and registered as meeting the requirements of BS EN ISO 9001 : 2015 by BSI (Certificate FM 45536).

## 3 Delivery and site handling

3.1 Rolls are delivered to site individually wrapped in polythene. A technical leaflet bearing the product name and the BBA logo incorporating the number of this Certificate is included with each roll.

3.2 The rolls should be stored flat or on end on a smooth, clean, dry surface, under cover and protected from sunlight.

## Assessment and Technical Investigations

The following is a summary of the assessment and technical investigations carried out on Breathable FrameTX Maxi for use in timber frame construction.

### Design Considerations

## 4 Use

4.1 Breathable FrameTX Maxi for use in timber frame construction is satisfactory for use as an on-site or factory-applied breather membrane in timber frame walls with a cavity and a masonry outer leaf, weatherboarding or tile/slate cladding.

4.2 In the absence of other guidance, suitable timber frame walls are defined as those designed and built in accordance with *NHBC Standards* 2018, Chapter 6.2.

4.3 The product satisfies the requirements for a Class W1 material in accordance with BS EN 13859-2 : 2014 and the NHBC requirements given in *NHBC Standards* 2018, Chapter 6.2, as a high-performance breather membrane for use in very severe conditions<sup>(1)</sup>.

(1) Very severe conditions are defined in *NHBC Standards* 2018, Figure 1 Exposure zones map showing categories of exposure to wind-driven rain.

## 5 Practicability of installation

The product is designed to be installed by a competent builder experienced with this type of product.

## 6 Weathertightness



6.1 The product is classified as Class W1\* in accordance with BS EN 13859-2 : 2014. The product will resist liquid water penetration and wind-blown snow, and will protect the sheathing from external moisture.

6.2 The product can be used as temporary weather protection during construction, prior to the completion of external brickwork or claddings. The period of such use should, however, be kept to a minimum. Advice should be sought from the Certificate holder.

## 7 Risk of condensation



7.1 For design purposes, the product has a resistance to water vapour transmission of less than or equal to  $0.6 \text{ MN}\cdot\text{s}\cdot\text{g}^{-1}$ , and is classified as breather membranes in accordance with BS 5250 : 2011. Walls incorporating the product will therefore adequately limit the risk of interstitial condensation when designed and constructed in accordance with BS 5250 : 2011, Annex G.

7.2 The risk of condensation occurring within the wall of a timber frame building will depend upon the properties and vapour resistance of other materials used in the construction, the internal and external conditions and the effectiveness of the internal vapour control layer.

## 8 Strength

8.1 The product will resist the normal loads associated with construction and installation of timber frame construction.

8.2 The product is not adversely affected by water and will retain its mechanical properties when wet.

## 9 Properties in relation to fire

9.1 The product achieves a Class D, d2\* classification in accordance with BS EN 13501-1 : 2002.

9.2 The product will have similar properties to polyolefin membranes in relation to fire, tending to burn and shrink away from the heat source. The product is unclassifiable in terms of the national Building Regulations and this should be considered when assessing the overall fire risk.

9.3 Cavity barriers should be used to satisfy the requirements of the national Building Regulations.

## 10 Maintenance

As the product is confined within the wall space and has suitable durability, maintenance is not required. However, any damage occurring before enclosure must be repaired (see section 15).

## 11 Durability



The product will be virtually unaffected by the normal conditions found in timber frame walls and will have a life equal to that of the building in which it is installed.

## 12 Reuse and recyclability

The product contains polyolefins, which can be recycled.

## Installation

### 13 General


Breathable FrameTX Maxi for use in timber frame construction must be installed in accordance with the Certificate holder's instructions and the recommendations given in *NHBC Standards 2018*, Chapter 6.2, where appropriate.

### 14 Procedure

14.1 The product must be secured at regular intervals not exceeding 500 mm with austenitic stainless steel staples or nails to prevent damage by wind action.

14.2 Upper layers should overlap lower layers to shed water away from the sheathing. Vertical laps should be staggered wherever possible (see Figure 1).

Figure 1 Membrane installation- Fixing distances



14.3 Horizontal laps should be at least 100 mm and vertical laps 150 mm.

14.4 It is essential that the positions of studs are marked on the face of the breather membrane, preferably by tape, to enable fixing of wall ties or battens.

14.5 It is essential that the lowest timbers in the wall are protected by the breather membrane.

## 15 Repair

The product can be damaged by careless handling, high winds or vandalism. Damage to the membrane can be repaired prior to the installation of external walls or claddings by laying another sheet over the damaged areas and sealing it correctly, ensuring that water is shed away from the sheathing.

## Technical Investigations

### 16 Tests

An assessment was made of data to BS EN 13859-2 : 2014 in relation to:

- dimensions
- mass per unit area
- tensile strength and elongation
- resistance to tear
- dimensional stability
- resistance to water penetration
- resistance to artificial ageing
- resistance to penetration of air.

### 17 Investigations

The manufacturing process was evaluated, including the methods adopted for quality control, and details were obtained of the quality and composition of the materials used.

## Bibliography

BS 5250 : 2011 + A1 : 2016 *Code of practice for control of condensation in buildings*

BS EN 13501-1 : 2002 *Fire classification of construction products and building elements — Classification using test data from reaction to fire tests*

BS EN 13859-2 : 2014 *Flexible sheet for waterproofing — Definitions and characteristics of underlays — Underlays for walls*

BS EN ISO 9001 : 2015 *Quality management systems — Requirements*

### 18 Conditions

18.1 This Certificate:

- relates only to the product/system that is named and described on the front page
- is issued only to the company, firm, organisation or person named on the front page – no other company, firm, organisation or person may hold claim that this Certificate has been issued to them
- is valid only within the UK
- has to be read, considered and used as a whole document – it may be misleading and will be incomplete to be selective
- is copyright of the BBA
- is subject to English Law.

18.2 Publications, documents, specifications, legislation, regulations, standards and the like referenced in this Certificate are those that were current and/or deemed relevant by the BBA at the date of issue or reissue of this Certificate.

18.3 This Certificate will remain valid for an unlimited period provided that the product/system and its manufacture and/or fabrication, including all related and relevant parts and processes thereof:

- are maintained at or above the levels which have been assessed and found to be satisfactory by the BBA
- continue to be checked as and when deemed appropriate by the BBA under arrangements that it will determine
- are reviewed by the BBA as and when it considers appropriate.

18.4 The BBA has used due skill, care and diligence in preparing this Certificate, but no warranty is provided.

18.5 In issuing this Certificate the BBA is not responsible and is excluded from any liability to any company, firm, organisation or person, for any matters arising directly or indirectly from:

- the presence or absence of any patent, intellectual property or similar rights subsisting in the product/system or any other product/system
- the right of the Certificate holder to manufacture, supply, install, maintain or market the product/system
- actual installations of the product/system, including their nature, design, methods, performance, workmanship and maintenance
- any works and constructions in which the product/system is installed, including their nature, design, methods, performance, workmanship and maintenance
- any loss or damage, including personal injury, howsoever caused by the product/system, including its manufacture, supply, installation, use, maintenance and removal
- any claims by the manufacturer relating to CE marking.

18.6 Any information relating to the manufacture, supply, installation, use, maintenance and removal of this product/system which is contained or referred to in this Certificate is the minimum required to be met when the product/system is manufactured, supplied, installed, used, maintained and removed. It does not purport in any way to restate the requirements of the Health and Safety at Work etc. Act 1974, or of any other statutory, common law or other duty which may exist at the date of issue or reissue of this Certificate; nor is conformity with such information to be taken as satisfying the requirements of the 1974 Act or of any statutory, common law or other duty of care.