

# Technical Datasheet

During internal works and renovations, protecting any existing carpets and flooring from accidental damage is essential. Loosely laid around the work area, FloorTX® FR is a single-layer, nonwoven spunbond with an added flame retardant treatment used in protective flooring, furniture and bedding (non-visible). This product is also a long-lasting, durable treatment.

FloorTX® FR inhibits and resists the spread of fire while being compliant with the relevant British standards.

|  | Test Method    | FloorTX® FR |      |
|--|----------------|-------------|------|
| <b>Fabric weight (g/m<sup>2</sup>)</b> | NWSP 130.1     | 50          | 100* |
| <b>Tensile Strength (N)</b>            | NWSP 110.4     | <b>MD</b>   | 130  |
|  |                | <b>CD</b>   | 90   |
| <b>Tear Strength (N)</b>               | ASTM D1424-07a | 8           | 10   |
| <b>Fire Retardant</b>                  | BS 7175        | Source 5    |      |

\*100g/m<sup>2</sup> Grey(E5)TFR certified by the BRE Loss Prevention Certification Board (726a/02) as Daltex FR.  
MD = machine direction, CD = cross/transverse direction

Other weights are available on request.

## All products are manufactured under BS EN ISO 9001.

Don & Low reserves the right to change specifications or other product information. Don & Low accepts no responsibility or liability for information provided by third parties. No warranties, express or implied, are offered regarding the suitability of any product for your use, as site conditions and customer requirements vary. Should you require further information, please contact us. Products are sold subject to the seller's terms and conditions of sale. No warranty or immunity is offered against infringement of patents or other intellectual property rights. ©Don & Low Limited, 2025. The intellectual property in the products is owned and protected by Don & Low or its licensors.