

Don & Low Roofing Accessories

TLE Handed Dry Verge

Datasheet


The Don & Low TLE Handed Dry Verge is designed to provide a mortar free and secure method of fixing concrete interlocking verge tiles whilst complying to BS5534. It provides a consistent appearance that requires no maintenance. The system is available in two colours and fits concrete interlocking tiles, between 260-350mm batten gauge and tested to BS8612.

Guidelines

The TLE Handed Dry Verge requires the Starter piece at the eaves. It is also available with compatible Half Round or Angled End Caps. Tile battens must be set out as per the fixing instructions and Verge units must be screw fixed.

Specifications			
	TLE Handed Dry Verge	TLE Handed Dry Verge Starter	Dry Verge End Cap
Product Code	DL2TLEV	DL2TLEVS	DL2ECR & DL2ECA
Weight	162g	48.6g	140g
Dimensions	400x140mm	??????	240x260mm
Pcs / Carton	50	25	40
Cartons / Pallet	20	40	20
Material	Polypropylene (PP)		
Manufacturing Process	Injection Moulding		
Colours	Grey, Black		
Regulations / Certifications	Compliant with All Relevant British Standards and Regulations		

ISSUE DATE: DECEMBER 2025



Construction Technical Services

0808 169 4444

Don & Low Ltd, Glamis Road, Forfar, Angus, DD8 1FR, Scotland, UK
Tel: +44(0)1307 452200 Fax: +44 (0)1307 452201

Don & Low assumes no liability for written errors within this document.



All products are covered by 15 Year Durability Warranty. Terms and conditions apply.



All plastic products are made in the UK.