

Fixing Instructions

Plain Tile Vent



Plain Tile Ulti-Match Vent



1 Decide position where the vent is to be installed.
Note: this should not clash with a rafter. Mark and cut the membrane with an "X" between two battens.




7 Identify where Ulti-Match Vent is to be fitted.
Note that this vent is also ideal for "retro fit" on old or obsolete tiles.



2 Fold the top envelope section of the membrane from your "X" cut, over the top batten. Secure into position with a felt tack into the batten.



8 Expose the area where the vent is to be fitted and follow point 1 and 2 on cutting and fixing the membrane.



3 Select vent colour to suit tiles and if being used for extraction also select the Plain Vent Tile Adaptor DL3PTVA and Flexipipe DL3FP. **Note:** Do not fix adaptor at this time.



9 Position the vent and cut two matching pieces of tile 75mm in length ready to adhere to.



4 Position the vent in the roof and secure through the top fixing point into the batten. If an adaptor is needed, fit this from the underside.



10 Use a suitable sealant (this sealant must adhere to ASA Plastic and to the finish of tile). Apply sealant to backside of cut tiles and firmly press onto the tail of Vent.



5 Start to lay tiles around the vent ensuring that these are nailed in line with the tile manufacturer's recommended nail size.



11 Once the cut sections of tile are adhered, run a sealant strip onto the top edge and then allow the sealant to fully adhere.



6 Repeat above steps as necessary should further vents be required.



12 Repeat above steps as necessary should further vents be required. Complete the roof and, if required, fit the Plain Vent Tile Adaptor DL3PTVA and Flexipipe DL3FP to the underside of the vent.

Construction Technical Services

0808 169 4444

Don & Low Ltd, Glamis Road, Forfar, Angus, DD8 1FR, Scotland, UK
Tel: +44(0)1307 452200 Fax: +44 (0)1307 452201

Don & Low assumes no liability for written errors within this document.

15 YEAR
WARRANTY

All products are covered by 15 year Durability Warranty. Terms and conditions apply.



All plastic products are made in the UK.